CONFIGURATION GUIDES › DOCKER

Install Applicare SingleAgent in DebianOS

Applicare 10.0 · Updated October 16, 2024 · docker, singleagent, linux · **Pending technical review**

Step 1: Insert the following scripts immediately after the FROM command in the Dockerfile.

RUN yum update && \ yum -y install wget unzip net-toolsRUN mkdir /usr/local/Applicare WORKDIR /usr/local/Applicare RUN curl **CONTROLLER_PROTOCOL**://**CONTROLLER_IP:CONTROLLER_PORT**/applicare/standalone?filename=ApplicareSingleAgentLinux.zip >ApplicareSingleAgentLinux.zip RUN unzip ApplicareSingleAgentLinux.zip RUN ["rm", "-frv", "/usr/local/Applicare/ApplicareSingleAgentLinux.zip"] WORKDIR /usr/local/Applicare WORKDIR /usr/local/Applicare/wrapper/linux RUN chmod +x install.sh RUN chmod -R 777 /usr/local/Applicare RUN ["/usr/local/Applicare/wrapper/linux/install.sh"]

Replace the below values in the above script

CONTROLLER_PROTOCOL -> http (or) https

CONTROLLER_IP -> Applicare Controller IP

CONTROLLER_PORT -> Applicare Controller Port

Example:

```bash
FROM tomcat:8
RUN yum update && \
    yum –y install wget unzip
RUN mkdir /usr/local/Applicare
WORKDIR /usr/local/Applicare
RUN curl http://127.0.0.1:8880/applicare/standalone?filename=ApplicareSingleAgentLinux.zip
>ApplicareSingleAgentLinux.zip
RUN unzip ApplicareSingleAgentLinux.zip
RUN ["rm", "–frv", "/usr/local/Applicare/ApplicareSingleAgentLinux.zip"]
WORKDIR /usr/local/Applicare
WORKDIR /usr/local/Applicare/wrapper/linux
RUN chmod +x install.sh
RUN ["/usr/local/Applicare/wrapper/linux/install.sh"]
```

Step 2: Add server name while creating a Docker container.

When creating the Docker container, set the server name as an environment variable using **-e sname= <SERVERNAME> and start the container. Replace <SERVERNAME> with the name you want to assign to the agent in Applicare.** The **<SERVERNAME>** should be unique for each container.

e.g.

-e sname=tomcatcontainer

BASH

```
docker container run –it –d –p 8065:8080 ––name container1 –e sname=tomcatcontainer
1a28b359235a
```