CONFIGURATION GUIDES › .NET

# Monitoring Containerized .NET Applications with Applicare and OpenTelemetry

Applicare 10.0 · Updated July 14, 2025 · dotnet, docker, opentelemetry · **Pending technical review**

To enable OpenTelemetry auto-instrumentation for your .NET application and send traces to Applicare, you will need to apply configuration changes in both your **Dockerfile** and your application's **YAML deployment script** (e.g., Kubernetes Deployment, Docker Compose file, or other container orchestration tool's configuration).

## Step 1: Modify your Dockerfile

Add the following lines to your application's Dockerfile. These commands will install necessary utilities, download the OpenTelemetry .NET auto-instrumentation setup script, execute it.

**Note:** The `apt-get` commands assume a Debian/Ubuntu-based base image (e.g., `mcr.microsoft.com/dotnet/aspnet:8.0-alpine` would use `apk add --no-cache` instead). Adjust package manager commands as per your base image.

```
TEXT
ENV OTEL_AGENT_VERSION=1.9.0
ENV DOTNET_EnableDiagnostics=1
ENV OTEL_DOTNET_AUTO_HOME=/otel-dotnet-auto
ENV DOTNET_SHARED_STORE=$OTEL_DOTNET_AUTO_HOME/store
ENV
DOTNET_STARTUP_HOOKS=$OTEL_DOTNET_AUTO_HOME/net/OpenTelemetry.AutoInstrumentation.StartupHook
.dll
ENV DOTNET_ADDITIONAL_DEPS=$OTEL_DOTNET_AUTO_HOME/AdditionalDeps
ENV OTEL_TRACES_EXPORTER=otlp
ENV OTEL_DOTNET_AUTO_LOGGING_ENABLED=true
ENV OTEL_DOTNET_AUTO_ENTITYFRAMEWORKCORE_SET_DBSTATEMENT_FOR_TEXT=true
ENV OTEL_DOTNET_AUTO_SQLCLIENT_SET_DBSTATEMENT_FOR_TEXT=true
ENV COMPlus_EnableDiagnostics=1
ENV DOTNET_EnableDiagnostics=1
ENV DOTNET_ROLL_FORWARD=LatestMajor

RUN apt-get update && apt-get install -y unzip curl
ADD https://github.com/open-telemetry/opentelemetry-dotnet-
instrumentation/releases/download/v1.9.0/otel-dotnet-auto-install.sh /otel-install.sh

RUN chmod +x /otel-install.sh && \
    /otel-install.sh
```

## Step 2: Configure Environment Variables in your YAML Deployment

Add the following environment variables to the container definition section of your application's YAML deployment file (e.g., under `env:` in a Kubernetes `Deployment`'s container specification, or `environment:` in a Docker Compose `service`). These variables instruct the OpenTelemetry auto-instrumentation how to behave and where to send the telemetry data.

```
TEXT
OTEL_DOTNET_AUTO_HOME="/otel-dotnet-auto"
DOTNET_SHARED_STORE="/otel-dotnet-auto/store"
DOTNET_STARTUP_HOOKS="/otel-dotnet-
auto/net/OpenTelemetry.AutoInstrumentation.StartupHook.dll"
DOTNET_ADDITIONAL_DEPS="/otel-dotnet-auto/AdditionalDeps"
OTEL_TRACES_EXPORTER="otlp"
OTEL_EXPORTER_OTLP_ENDPOINT="http://<APPLICARE_CONTROLLER_IP>:4318"
OTEL_SERVICE_NAME="<APPLICARE_AGENT_NAME>"
OTEL_DOTNET_AUTO_ENTITYFRAMEWORKCORE_SET_DBSTATEMENT_FOR_TEXT="true"
OTEL_DOTNET_AUTO_SQLCLIENT_SET_DBSTATEMENT_FOR_TEXT="true"
```

**Before deploying your application, ensure you replace the following placeholders:**

- `<APPLICARE_CONTROLLER_IP>`: Replace this with the actual IP address or hostname of your Applicare controller instance.
- `<APPLICARE_AGENT_NAME>`: Provide a unique, descriptive name that will help you identify this specific container or application within the Applicare monitoring console.

**Sample Dockerfile with the above changes.**

```
# See https://aka.ms/customizecontainer to learn how to customize your debug container and how Visual Studio uses this Dockerfile to build your imag

# This stage is used when running from VS in fast mode (Default for Debug configuration)
FROM mcr.microsoft.com/dotnet/aspnet:8.0 AS base

ENV OTEL_AGENT_VERSION=1.9.0
ENV DOTNET_EnableDiagnostics=1
ENV OTEL_DOTNET_AUTO_HOME=/otel-dotnet-auto
ENV DOTNET_SHARED_STORE=$OTEL_DOTNET_AUTO_HOME/store
ENV DOTNET_STARTUP_HOOKS=$OTEL_DOTNET_AUTO_HOME/net/OpenTelemetry.AutoInstrumentation.StartupHook.dll
ENV DOTNET_ADDITIONAL_DEPS=$OTEL_DOTNET_AUTO_HOME/AdditionalDeps
ENV OTEL_TRACES_EXPORTER=otlp
ENV OTEL_DOTNET_AUTO_LOGGING_ENABLED=true
ENV OTEL_DOTNET_AUTO_ENTITYFRAMEWORKCORE_SET_DBSTATEMENT_FOR_TEXT=true
ENV OTEL_DOTNET_AUTO_SQLCLIENT_SET_DBSTATEMENT_FOR_TEXT=true
ENV COMPlus_EnableDiagnostics=1
ENV DOTNET_EnableDiagnostics=1
ENV DOTNET_ROLL_FORWARD=LatestMajor

RUN apt-get update && apt-get install -y unzip curl
ADD https://github.com/open-telemetry/opentelemetry-dotnet-instrumentation/releases/download/v1.9.0/otel-dotnet-auto-install.sh /otel-install.sh

RUN chmod +x /otel-install.sh && \
    /otel-install.sh

USER $APP_UID
WORKDIR /app
EXPOSE 8080

# This stage is used to build the service project
FROM mcr.microsoft.com/dotnet/sdk:8.0 AS build
ARG BUILD_CONFIGURATION=Release
WORKDIR /src
COPY ["WebApplication1/WebApplication1.csproj", "WebApplication1/"]
#COPY ["WebApplication1.csproj", "WebApplication1/"]
RUN dotnet restore "./WebApplication1/WebApplication1.csproj"
COPY . .
WORKDIR "/src/WebApplication1"
RUN dotnet build "./WebApplication1.csproj" -c $BUILD_CONFIGURATION -o /app/build

# This stage is used to publish the service project to be copied to the final stage
```

**Sample YAML with the above changes.**

```yaml
      app: applicareapp
  template:
    metadata:
      labels:
        app: applicareapp
    spec:
      containers:
        - name: webapplication1
          image: applicare910/applicareapp:webapplicationwithenv
          ports:
            - containerPort: 8080
          env:
            - name: OTEL_DOTNET_AUTO_HOME
              value: "/otel-dotnet-auto"
            - name: DOTNET_SHARED_STORE
              value: "/otel-dotnet-auto/store"
            - name: DOTNET_STARTUP_HOOKS
              value: "/otel-dotnet-auto/net/OpenTelemetry.AutoInstrumentation.StartupHook.dll"
            - name: DOTNET_ADDITIONAL_DEPS
              value: "/otel-dotnet-auto/AdditionalDeps"
            - name: OTEL_TRACES_EXPORTER
              value: "otlp"
            - name: OTEL_EXPORTER_OTLP_ENDPOINT
              value: "http://192.168.0.117:4318"
            - name: OTEL_SERVICE_NAME
              value: "Applicare_demo"
            - name: OTEL_DOTNET_AUTO_ENTITYFRAMEWORKCORE_SET_DBSTATEMENT_FOR_TEXT
              value: "true"
            - name: OTEL_DOTNET_AUTO_SQLCLIENT_SET_DBSTATEMENT_FOR_TEXT
              value: "true"
---
apiVersion: v1
kind: Service
metadata:
  name: applicareapp
  namespace: applicare-ns
spec:
  selector:
    app: applicareapp
  ports:
    - protocol: TCP
```