CONFIGURATION GUIDES › KUBERNETES

Monitoring Nginx in a Kubernetes

Applicare 10.0 · Updated May 9, 2026 · kubernetes, nginx · **Pending technical review**

Step 1: Add the following line next to the **From** line in the **Dockerfile** that builds Nginx.

```bash
RUN apt-get update && \
apt-get install unzip -y && \
apt-get install curl -y && \
apt-get clean

RUN mkdir /usr/local/Applicare
WORKDIR /usr/local/Applicare
RUN curl $CONTROLLER_PROTOCOL://$CONTROLLER_IP:$CONTROLLER_PORT/applicare/standalone?
filename=ApplicareSingleAgentLinux >ApplicareSingleAgentLinux.zip
RUN unzip ApplicareSingleAgentLinux.zip
RUN ["rm", "-frv", "/usr/local/Applicare/ApplicareSingleAgentLinux.zip"]
COPY startAgent.sh /usr/local/Applicare/agentscripts/startAgent.sh
COPY start_nginx.sh /usr/local/Applicare/start_nginx.sh
RUN chmod -R 755 /usr/local/Applicare
WORKDIR /usr/local/Applicare
CMD ["./start_nginx.sh"]
```

Replace the below values in the above command

CONTROLLER_PROTOCOL -> http (or) https

CONTROLLER_IP -> Applicare Controller IP

CONTROLLER_PORT -> Applicare Controller Port

Step 2: Create a file named **start_nginx.sh** with the following content:

```bash
#!/bin/bash# Start Nginx in the backgroundnginx -g "daemon off;" &# Start our
Agent/usr/local/Applicare/startAgent.sh
```

Step 3: Create a file named **startAgent.sh** with the content below.

BASH

```
#!/bin/sh
SERVER_NAME=`hostname`_sa

export SERVER_NAME

if [ -z "$ARCTURUS_HOME" ]; then

ARCTURUS_HOME="/usr/local/Applicare"

fi

export ARCTURUS_HOME

JAVA_HOME_PATH=$JAVA_HOME

INBUILD_JAVA_PATH=$ARCTURUS_HOME/jre

export INBUILD_JAVA_PATH

if [[ $(uname -s) == "Darwin" ]]; then

  JAVA_HOME_PATH="$ARCTURUS_HOME/jre/mac/zulu-8_jre/Contents/Home"

else

  JAVA_HOME_PATH="$ARCTURUS_HOME/jre/linux/jre"

fi

#export JAVA_HOME

export JAVA_HOME_PATH

JAVA_OPTS="-noverify -Xmx1024m -Dserver.name=$SERVER_NAME -
javaagent:$ARCTURUS_HOME/applicare-db-aspects.jar=verbosity=0,logfile=false,norestart-
intellitrace=false -Darcturus_home=$ARCTURUS_HOME -XX:HeapDumpPath=/dev/null -
Djava.library.path=.:$ARCTURUS_HOME/bin -Dapplicare.standalone=true"

export JAVA_OPTS

EXECUTABLE_NAME=$ARCTURUS_HOME/AgentStartHelper.jar

export EXECUTABLE_NAME
```

```
if [ -d "$JAVA_HOME_PATH/bin" ] ; then

 "$JAVA_HOME_PATH/bin"/java -jar $JAVA_OPTS $EXECUTABLE_NAME

else

 java -jar $JAVA_OPTS $EXECUTABLE_NAME

fi
```

Step 4: In the `nginx.conf` file, make the following changes:

a.) Comment out the existing `log_format` directive and add the new `log_format` as shown below.

```
TEXT
log_format  main  '$remote_addr - $remote_user $time_iso8601 [$request_time] "$request" '
'$status $body_bytes_sent "$http_referer" '                    '"$http_user_agent"
"$http_x_forwarded_for"';
```

```
http {
    #log_format  main  '$remote_addr - $remote_user [$time_local] "$request" '
    #                  '$status $body_bytes_sent "$http_referer" '
    #                  '"$http_user_agent" "$http_x_forwarded_for"';

    log_format  main  '$remote_addr - $remote_user $time_iso8601 [$request_time] "$request" '
                      '$status $body_bytes_sent "$http_referer" '
                      '"$http_user_agent" "$http_x_forwarded_for"';

    access_log  /var/log/nginx/access.log  main;

    sendfile            on;
    tcp_nopush          on;
    tcp_nodelay         on;
    keepalive_timeout   65;
    types_hash_max_size 2048;
```

b.) Uncomment the **access_log** line if it is already commented.

```
    #log_format  main  '$remote_addr - $remote_user [$time_local] "$request" '
    #                  '$status $body_bytes_sent "$http_referer" '
    #                  '"$http_user_agent" "$http_x_forwarded_for"';

    log_format  main  '$remote_addr - $remote_user $time_iso8601 [$request_time] "$request" '
                      '$status $body_bytes_sent "$http_referer" '
                      '"$http_user_agent" "$http_x_forwarded_for"';

    access_log  logs/access.log  main;
```

c.) Add the below lines inside the **server** module

```
TEXT
location /nginx-status {stub_status on;allow 127.0.0.1;}
```

```
server {
    listen       80;
    #listen       [::]:83;
    listen       127.0.0.1:80;

    server_name  _;
    root         /usr/share/nginx/html;

    # Load configuration files for the default server block.
    include /etc/nginx/default.d/*.conf;

    error_page 404 /404.html;
    location = /404.html {
    }

    error_page 500 502 503 504 /50x.html;
    location = /50x.html {
    }

    location /nginx-status {
    stub_status on;
    allow 127.0.0.1;
    }
}
```

Step 5: Add the following line to the container specification in the YAML file that starts Nginx on Kubernetes.

```
TEXT
hostname: <hostname>
```

Replace **<hostname>** with the name which we need to add the agent in Applicare.

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: nginx-ubuntug-deployment
  namespace: nginx-ubuntu
spec:
  replicas: 1
  selector:
    matchLabels:
      app: nginx-ubuntu
  template:
    metadata:
      labels:
        app: nginx-ubuntu
    spec:
      hostname: nginx-ubuntu
      containers:
      - name: nginx-ubuntu
        image: nginx-ubuntu:latest
        ports:
        - containerPort: 80
```

Step 6: Log in to the Applicare console, go to the **Overview** menu, select the newly added agent, and click the **Edit** button.

Step 7: Enable the "**Add Nginx Configuration**" checkbox and add the below value.

1. Log file path - <**access log file location**>

2. Nginx Host - 127.0.0.1

3. Nginx Port - <**Nginx_Port**>

4. Nginx Protocol - http (or) https

Click the **update** button to save.