CONFIGURATION GUIDES › OPENTELEMETRY

Monitor Traces and Metrics in Containerized .NET Applications with Applicare and OpenTelemetry

Applicare 10.0 · Updated August 22, 2025 · opentelemetry, dotnet, docker · **Pending technical review**

To enable OpenTelemetry auto-instrumentation for your .NET application and send traces to Applicare, you will need to apply configuration changes in both your **Dockerfile** and your application's **YAML deployment script** (e.g., Kubernetes Deployment, Docker Compose file, or other container orchestration tool's configuration).

Step 1: Modify your Dockerfile

Add the following lines to your application's Dockerfile. These commands will install necessary utilities, download the OpenTelemetry .NET auto-instrumentation setup script, and Applicare.NetTrace setup, execute it.

Add the Diagnostic tools stage below before the FROM base AS final (or) FROM runtime AS final stage

```text
# Diagnostic tools stage
FROM mcr.microsoft.com/dotnet/sdk:8.0 AS diagnostic-tools
RUN dotnet tool install --tool-path /dotnet-tools dotnet-counters \
&& dotnet tool install --tool-path /dotnet-tools dotnet-trace \
&& dotnet tool install --tool-path /dotnet-tools dotnet-dump
```

```
# See https://aka.ms/customizecontainer ...
FROM mcr.microsoft.com/dotnet/aspnet:8.0 AS base
USER $APP_UID
WORKDIR /app
EXPOSE 8080

FROM mcr.microsoft.com/dotnet/sdk:8.0 AS build
ARG BUILD_CONFIGURATION=Release
WORKDIR /src
COPY ["WebApplication1/WebApplication1.csproj", "WebApplication1/"]
RUN dotnet restore "./WebApplication1/WebApplication1.csproj"
COPY . .
WORKDIR "/src/WebApplication1"
RUN dotnet build "./WebApplication1.csproj" -c $BUILD_CONFIGURATION -o /app/build

FROM build AS publish
ARG BUILD_CONFIGURATION=Release
RUN dotnet publish "./WebApplication1.csproj" -c $BUILD_CONFIGURATION -o /app/publish /p:UseAppHost=false

#Diagnostic tools stage ✅ PLACE IT HERE
FROM mcr.microsoft.com/dotnet/sdk:8.0 AS diagnostic-tools
RUN dotnet tool install --tool-path /dotnet-tools dotnet-counters \
 && dotnet tool install --tool-path /dotnet-tools dotnet-trace \
 && dotnet tool install --tool-path /dotnet-tools dotnet-dump

FROM base AS final
WORKDIR /app
```

Note: The `apt-get` commands assume a Debian/Ubuntu-based base image (e.g., `mcr.microsoft.com/dotnet/aspnet:8.0-alpine` would use `apk add --no-cache` instead). Adjust package manager commands as per your base image.

Below lines should be added inside final runtime stage, and specifically after FROM base AS final (or) FROM runtime AS final

```
TEXT
ENV OTEL_AGENT_VERSION=1.9.0
ENV DOTNET_EnableDiagnostics=1
ENV OTEL_DOTNET_AUTO_HOME=/otel-dotnet-auto
ENV DOTNET_SHARED_STORE=$OTEL_DOTNET_AUTO_HOME/store
ENV
DOTNET_STARTUP_HOOKS=$OTEL_DOTNET_AUTO_HOME/net/OpenTelemetry.AutoInstrumentation.StartupHook
.dll
ENV DOTNET_ADDITIONAL_DEPS=$OTEL_DOTNET_AUTO_HOME/AdditionalDeps
```

```
#Diagnostic tools stage  ✅  PLACE IT HERE
FROM mcr.microsoft.com/dotnet/sdk:8.0 AS diagnostic-tools
RUN dotnet tool install --tool-path /dotnet-tools dotnet-counters \
 && dotnet tool install --tool-path /dotnet-tools dotnet-trace \
 && dotnet tool install --tool-path /dotnet-tools dotnet-dump

FROM base AS final
WORKDIR /app

ENV OTEL_AGENT_VERSION=1.9.0
ENV DOTNET_EnableDiagnostics=1
ENV OTEL_DOTNET_AUTO_HOME=/otel-dotnet-auto
ENV DOTNET_SHARED_STORE=$OTEL_DOTNET_AUTO_HOME/store
ENV DOTNET_STARTUP_HOOKS=$OTEL_DOTNET_AUTO_HOME/net/OpenTelemetry.AutoInstrumentation.StartupHook.dll
ENV DOTNET_ADDITIONAL_DEPS=$OTEL_DOTNET_AUTO_HOME/AdditionalDeps
```

a.) If "USER $APP_UID" already exists in the Dockerfile, add the following lines after the ENV stage.

```
TEXT
USER root
RUN apt-get update && apt-get install -y unzip curl
ADD https://github.com/open-telemetry/opentelemetry-dotnet-
instrumentation/releases/download/v1.9.0/otel-dotnet-auto-install.sh /otel-install.sh
RUN chmod +x /otel-install.sh && \
   /otel-install.sh
RUN curl -L https://applicare.blob.core.windows.net/demoapplication/arc_dotnet.zip -o
arc_dotnet.zip \
&& unzip arc_dotnet.zip -d arc_dotnet \
&& rm arc_dotnet.zip
COPY --from=diagnostic-tools /dotnet-tools /dotnet-tools
ENV PATH="$PATH:/dotnet-tools"
ENV APPLICARE_URL=Protocol://ApplicareIP:ApplicarePort
USER $APP_UID
```

(OR)

b.) If "USER $APP_UID" not exists in the Dockerfile, add the following lines after the ENV stage.

```
TEXT
RUN apt-get update && apt-get install -y unzip curl ADD https://github.com/open-
telemetry/opentelemetry-dotnet-instrumentation/releases/download/v1.9.0/otel-dotnet-auto-
install.sh /otel-install.sh RUN chmod +x /otel-install.sh && \    /otel-install.sh

# Download and unzip arc_dotnet.zip
RUN curl -L https://applicare.blob.core.windows.net/demoapplication/arc_dotnet.zip -o
arc_dotnet.zip \
&& unzip arc_dotnet.zip -d arc_dotnet \
&& rm arc_dotnet.zip

# ✅ Copy diagnostic tools into runtime
COPY --from=diagnostic-tools /dotnet-tools /dotnet-tools

ENV PATH="$PATH:/dotnet-tools"
ENV APPLICARE_URL=Protocol://ApplicareIP:ApplicarePort # e.g. http://192.168.1.100:8880
```

```
ENV DOTNET_ADDITIONAL_DEPS=$OTEL_DOTNET_AUTO_HOME/AdditionalDeps
ENV OTEL_TRACES_EXPORTER=otlp
ENV OTEL_DOTNET_AUTO_LOGGING_ENABLED=true
ENV OTEL_DOTNET_AUTO_ENTITYFRAMEWORKCORE_SET_DBSTATEMENT_FOR_TEXT=true
ENV OTEL_DOTNET_AUTO_SQLCLIENT_SET_DBSTATEMENT_FOR_TEXT=true
ENV COMPlus_EnableDiagnostics=1
ENV DOTNET_EnableDiagnostics=1
ENV DOTNET_ROLL_FORWARD=LatestMajor

USER root

RUN apt-get update && \
    apt-get install -y curl unzip && \
    apt-get clean && \
    rm -rf /var/lib/apt/lists/*

ADD https://github.com/open-telemetry/opentelemetry-dotnet-instrumentation/releases/download/v1.9.0/otel-dotnet-auto-install.sh /otel-install.sh
RUN chmod +x /otel-install.sh && \
    /otel-install.sh

# Download and unzip arc_dotnet.zip
RUN curl -L https://applicare.blob.core.windows.net/demoapplication/arc_dotnet.zip -o arc_dotnet.zip \
 && unzip arc_dotnet.zip -d arc_dotnet \
 && rm arc_dotnet.zip

# ✅ Copy diagnostic tools into runtime
COPY --from=diagnostic-tools /dotnet-tools /dotnet-tools
ENV PATH="$PATH:/dotnet-tools"

ENV APPLICARE_URL=https://testenv.applicare.io:443
```

We need to add **ApplicareDotnetTrace.dll** to the Entrypoint and configure it to start.

```
TEXT
Before Update ENTRYPOINT in Dockerfile
ENTRYPOINT ["dotnet", WebApplication1.dll]

After Update ENTRYPOINT in Dockerfile
ENTRYPOINT sh -c "dotnet WebApplication1.dll & OTEL_DOTNET_AUTO_INSTRUMENTATION_ENABLED=false
dotnet ./arc_dotnet/ApplicareDotnetTrace.dll"
```

```
USER $APP_UID
COPY --from=publish /app/publish .

ENTRYPOINT sh -c "dotnet WebApplication1.dll & OTEL_DOTNET_AUTO_INSTRUMENTATION_ENABLED=false  dotnet ./arc_dotnet/ApplicareDotnetTrace.dll"
```

Step 2: Install Opentelemetry collector in your Kubernetes cluster. Download the yaml file and change **<Applicare_Ip>** in that yaml file.

If have Wget, execute the command below.

```
BASH
sudo wget
https://applicare.blob.core.windows.net/demoapplication/opentelemetry_collector.yaml
```

```
TEXT
                                                                **(OR)**
```

If have Curl, execute the command below.

```
BASH
sudo curl -O
https://applicare.blob.core.windows.net/demoapplication/opentelemetry_collector.yaml
```

Then apply that yaml file to install collector in Kubernetes cluster.

```
BASH
kubectl apply -f opentelemetry_collector.yaml
```

Step 3: Configure Environment Variables in your YAML Deployment

Add the following environment variables to the container definition section of your application's YAML deployment file (e.g., under `env:` in a Kubernetes `Deployment`'s container specification, or `environment:` in a Docker Compose `service`). These variables instruct the OpenTelemetry auto-instrumentation how to behave and where to send the telemetry data.

YAML

```
          env:
            - name: OTEL_DOTNET_AUTO_HOME
              value: "/otel-dotnet-auto"
            - name: DOTNET_SHARED_STORE
              value: "/otel-dotnet-auto/store"
            - name: DOTNET_STARTUP_HOOKS
              value: "/otel-dotnet-
auto/net/OpenTelemetry.AutoInstrumentation.StartupHook.dll"
            - name: DOTNET_ADDITIONAL_DEPS
              value: "/otel-dotnet-auto/AdditionalDeps"
            # Kubernetes Metadata (Critical Fix)
            - name: KUBE_POD_NAME
              valueFrom:
                fieldRef:
                  fieldPath: metadata.name
            - name: KUBE_NAMESPACE
              valueFrom:
                fieldRef:
                  fieldPath: metadata.namespace
            # Resource Attributes (Updated)
            - name: OTEL_RESOURCE_ATTRIBUTES
              value: "k8s.pod.name=$(KUBE_POD_NAME),k8s.namespace.name=$(KUBE_NAMESPACE)"
            # Metrics Configuration
            - name: OTEL_METRICS_EXPORTER
              value: "otlp"
            - name: OTEL_DOTNET_AUTO_METRICS_ENABLED
              value: "true"
            - name: OTEL_EXPORTER_OTLP_ENDPOINT
              value: "http://otel-collector.monitoring.svc.cluster.local:4318"
            - name: OTEL_DOTNET_AUTO_METRICS_INCLUDE_PROCESS_RUNTIME
              value: "true"
            - name: OTEL_DOTNET_AUTO_METRICS_SET_SPECIFIC
              value:
"Microsoft.AspNetCore.Hosting[0],Microsoft.AspNetCore.Http.Connections[0]"
            - name: OTEL_DOTNET_AUTO_METRICS_ADDITIONAL_SOURCES
              value: "*"
            # Tracing Configuration
            - name: OTEL_TRACES_EXPORTER
              value: "otlp"
            # Instrumentation
            - name: OTEL_DOTNET_AUTO_ASPNETCORE_INSTRUMENTATION_ENABLED
              value: "true"
            - name: OTEL_DOTNET_AUTO_PROCESS_ENABLED
              value: "true"
```

```
        - name: OTEL_DOTNET_AUTO_HTTPCLIENT_ENABLED
          value: "true"
        - name: OTEL_DOTNET_AUTO_RUNTIMEMETRICS_ENABLED
          value: "true"
        - name: OTEL_DOTNET_AUTO_ENTITYFRAMEWORKCORE_SET_DBSTATEMENT_FOR_TEXT
          value: "true"
        - name: OTEL_DOTNET_AUTO_SQLCLIENT_SET_DBSTATEMENT_FOR_TEXT
          value: "true"
```

Sample YAML with the above changes.

```yaml
    app: applicareapp
  spec:
    containers:
      - name: webapplication1
        image: applicare910/applicareapp:dotnetcoregateway
        ports:
          - containerPort: 8080
        env:
          # OpenTelemetry Auto-Instrumentation
          - name: OTEL_DOTNET_AUTO_HOME
            value: "/otel-dotnet-auto"
          - name: DOTNET_SHARED_STORE
            value: "/otel-dotnet-auto/store"
          - name: DOTNET_STARTUP_HOOKS
            value: "/otel-dotnet-auto/net/OpenTelemetry.AutoInstrumentation.StartupHook.dll"
          - name: DOTNET_ADDITIONAL_DEPS
            value: "/otel-dotnet-auto/AdditionalDeps"
          # Kubernetes Metadata (Critical Fix)
          - name: KUBE_POD_NAME
            valueFrom:
              fieldRef:
                fieldPath: metadata.name
          - name: KUBE_NAMESPACE
            valueFrom:
              fieldRef:
                fieldPath: metadata.namespace
          # Resource Attributes (Updated)
          - name: OTEL_RESOURCE_ATTRIBUTES
            value: "k8s.pod.name=$(KUBE_POD_NAME),k8s.namespace.name=$(KUBE_NAMESPACE),k8s.deployment.name=$(KUBE_DEPLOYMENT_NAME)"
          # Metrics Configuration
          - name: OTEL_METRICS_EXPORTER
            value: "otlp"
          - name: OTEL_DOTNET_AUTO_METRICS_ENABLED
            value: "true"
          - name: OTEL_EXPORTER_OTLP_ENDPOINT
            value: "http://otel-collector.monitoring.svc.cluster.local:4318"
          - name: OTEL_DOTNET_AUTO_METRICS_INCLUDE_PROCESS_RUNTIME
            value: "true"
          - name: OTEL_DOTNET_AUTO_METRICS_SET_SPECIFIC
            value: "Microsoft.AspNetCore.Hosting[0],Microsoft.AspNetCore.Http.Connections[0]"
          - name: OTEL_DOTNET_AUTO_METRICS_ADDITIONAL_SOURCES
            value: "*"
          # Tracing Configuration
          - name: OTEL_TRACES_EXPORTER
            value: "otlp"
          # Instrumentation
          - name: OTEL_DOTNET_AUTO_ASPNETCORE_INSTRUMENTATION_ENABLED
            value: "true"
          - name: OTEL_DOTNET_AUTO_PROCESS_ENABLED
            value: "true"
          - name: OTEL_DOTNET_AUTO_HTTPCLIENT_ENABLED
            value: "true"
          - name: OTEL_DOTNET_AUTO_RUNTIMEMETRICS_ENABLED
            value: "true"
```

Step 4: On the machine running Applicare, download the shell script for below URL and give the executable permission for that shell script and execute the shell script.

If have Wget, execute the command below.

```bash
sudo wget
https://applicare.blob.core.windows.net/demoapplication/applicare_metric_collector_install.sh
```

```text
                                                                **(OR)**
```

If have Curl, execute the command below.

```bash
sudo curl -O
https://applicare.blob.core.windows.net/demoapplication/applicare_metric_collector_install.sh
```

The following port must be opened on the system where the Applicare controller is running.

9090 and 4318