CONFIGURATION GUIDES › APPLICATION SERVERS

Deploying SingleAgent for WebLogic on Windows

Applicare 9.2 · Updated March 23, 2026 · java, singleagent, windows · **Pending technical review**

1. **Install Applicare SingleAgent** on the machine where **Weblogic** is running.
   - **If Weblogic is started using startWebLogic.bat file follow these step.**
2. Navigate to the <**weblogic_domain_path**>\bin directory **startWebLogic.bat** file.
   - Go to <**weblogic_domain_path**>\bin directory and add the following line to the **startWebLogic.bat** file.

```bat
call <ApplicareSingleAgent_homepath>\scripts\setAgentEnv.bat
```

- **<ApplicareSingleagent_homepath>** - The directory where the Applicare SingleAgent zip file has been extracted.

```
187 echo ************************************************
188
189 echo *  To start WebLogic Server, use a username and   *
190
191 echo *  password assigned to an admin-level user.  For *
192
193 echo *  server administration, use the WebLogic Server *
194
195 echo *  console at http:\\hostname:port\console        *
196
197 echo ************************************************
198
199 @REM START WEBLOGIC
200
201 call D:\ApplicareSingleAgentWindows\scripts\setAgentEnv.bat
202
203
```

3. Restart Weblogic

Docs Home - Click here

Monitoring with Applicare