CONFIGURATION GUIDES › DATABASES

Automate Daily Batch Backups of few Tables Records to an Archive Database

Applicare 9.2 · Updated March 27, 2026 · mysql · **Pending technical review**

Step 1: Before backing up the database, create the **applicarearchive** schema, execute the applicare-related sql's and ensure all tables are created.

Step 2: Connect to the database via **MySQL Workbench**, open a new SQL query tab, and execute the following command.

NOTE: Replace the <targetDB> placeholder with actual backup database name before running the query.

YAML

```
DELIMITER //
DROP PROCEDURE IF EXISTS applicarearchive.sp_MasterArchive_Int_Profiling //
CREATE PROCEDURE applicarearchive.sp_MasterArchive_Int_Profiling()
BEGIN
   DECLARE v_done INT DEFAULT FALSE;
   DECLARE v_table_name VARCHAR(255);
   DECLARE v_id_col VARCHAR(100);
   DECLARE v_time_col VARCHAR(100);
   DECLARE v_source_db VARCHAR(100) DEFAULT '<targetDB>';
   DECLARE v_backup_db VARCHAR(100) DEFAULT 'applicarearchive';

   -- DATA MAP for selected tables only
   DECLARE table_cursor CURSOR FOR
       SELECT * FROM (
           SELECT 'intellitrace_errors' as t, 'id' as i, 'excep_at' as c UNION
           SELECT 'alert_queue', 'id', 'created_time' UNION
           SELECT 'int_profiling_hist', 'rl', 'from_time'
       ) mapping;

   DECLARE CONTINUE HANDLER FOR NOT FOUND SET v_done = TRUE;

   -- Ensure custom log table exists
   CREATE TABLE IF NOT EXISTS applicarearchive.archive_logcustom (
       id INT AUTO_INCREMENT PRIMARY KEY,
       table_name VARCHAR(255),
       rows_moved INT,
       sync_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
       status VARCHAR(255)
   );

   -- Target exactly 31 days ago (30 days before yesterday)
   SET @start_val = CONCAT(CURDATE() - INTERVAL 38 DAY, ' 00:00:00');
   SET @end_val   = CONCAT(CURDATE() - INTERVAL 38 DAY, ' 23:59:59');

   OPEN table_cursor;
   read_loop: LOOP
       FETCH table_cursor INTO v_table_name, v_id_col, v_time_col;
       IF v_done THEN LEAVE read_loop; END IF;

       SET @rows_affected = 1;
       SET @total_moved = 0;

       -- Move data in batches of 10,000 to prevent lag/locking
       WHILE @rows_affected > 0 DO
```

```
            SET @move_sql = CONCAT(
                'INSERT INTO ', v_backup_db, '.', v_table_name,
                ' SELECT * FROM ', v_source_db, '.', v_table_name,
                ' WHERE ', v_time_col, ' BETWEEN ? AND ? ',
                ' AND ', v_id_col, ' NOT IN (SELECT ', v_id_col, ' FROM ', v_backup_db, '.',
v_table_name, ') ',
                ' LIMIT 10000'
            );
            PREPARE m_stmt FROM @move_sql;
            EXECUTE m_stmt USING @start_val, @end_val;
            SET @rows_affected = ROW_COUNT();
            SET @total_moved = @total_moved + GREATEST(0, @rows_affected);
            DEALLOCATE PREPARE m_stmt;
        END WHILE;

        -- Log result into custom log table
        INSERT INTO applicarearchive.archive_logcustom (table_name, rows_moved, status)
        VALUES (
            CONCAT(v_table_name, ' (via ', v_time_col, ')'),
            @total_moved,
            IF(@total_moved > 0, 'SUCCESS', 'NO NEW DATA')
        );
    END LOOP;
    CLOSE table_cursor;
END //
DELIMITER ;
```

NOTE: The query above only backs up data from the few tables, rather than the entire database.

If you want to run the above stored procedure manually, execute the query below.

```
TEXT
CALL applicarearchive.sp_MasterArchive_Int_Profiling();
```

Step 3: Run the query below to enable the MySQL Event Scheduler and schedule the **sp_BatchArchiveYesterday** procedure to run daily at 1:00 AM.

```
TEXT
SET GLOBAL event_scheduler = ON;
DELIMITER //
DROP EVENT IF EXISTS applicarearchive.daily_archive_at_1am //
CREATE EVENT applicarearchive.daily_archive_at_1am
ON SCHEDULE EVERY 1 DAY
STARTS (CURRENT_DATE + INTERVAL 1 DAY + INTERVAL 1 HOUR)
DO
  BEGIN
    TRUNCATE TABLE applicarearchive.archive_log;
    CALL applicarearchive.sp_MasterArchive_Final();
  END //

DELIMITER ;
```

To modify the scheduled time, first execute the query below to drop the existing event, then re-create it with your desired schedule.

```
TEXT
DROP EVENT IF EXISTS applicarearchive.daily_archive_at_1am;
```

To change the time to 8:00 PM, We need to adjust the `INTERVAL` in the `STARTS` clause. Since MySQL uses a 24-hour format, 8:00 PM is 20 hours.


e.g.

```
TEXT
SET GLOBAL event_scheduler = ON;
DELIMITER //
DROP EVENT IF EXISTS applicarearchive.daily_archive_at_8pm //
CREATE EVENT applicarearchive.daily_archive_at_8pm
ON SCHEDULE EVERY 1 DAY
STARTS (CURRENT_DATE + INTERVAL 1 DAY + INTERVAL 20 HOUR)
DO
  BEGIN
    TRUNCATE TABLE applicarearchive.archive_log;
    CALL applicarearchive.sp_MasterArchive_Final();
  END //

DELIMITER ;
```

NOTE: Execute the below query to confirm the event is saved in the system.

```
TEXT
SHOW EVENTS FROM applicarearchive;
```



Db	Name	Definer	Time zone	Type	Execute at	Interval value	Interval field	Starts	Ends	Status	Originator	character_set_client	collation_connection	Database Collation
applicarearchive	setting_table_daily_archive_at_8pm	applicare@%	SYSTEM	RECURRING	NULL	1	DAY	2026-02-13 20:00:00	NULL	ENABLED	1	utf8mb4	utf8mb4_0900_ai_ci	utf8mb4_0900_ai_ci

Step 4: We need to create the `archive_log` table in your archive database. This table will record which table was processed, how many rows were moved, and exactly when it finished.


```
TEXT
CREATE TABLE IF NOT EXISTS applicarearchive.archive_logcustom (
    id INT AUTO_INCREMENT PRIMARY KEY,
    table_name VARCHAR(255),
    rows_moved INT,
    finish_time TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    status VARCHAR(255)
);
```

Explanation of the Columns:

- **id**: A unique number for every entry.
- **table_name**: Records the table name (and the column name used, e.g., `oshistory_detail [dt]`).
- **rows_moved**: The number of records successfully transferred for "Yesterday".
- **finish_time**: The exact date and time the backup for that specific table completed.

Step 5: Execute query to see the results. It will show you the most recent backups at the top.


```
TEXT
SELECT * FROM applicarearchive.archive_log ORDER BY finish_time DESC;
```



id	table_name	rows_moved	finish_time
3373	intellitrace_errors (via excep_at)	0	2026-02-10 15:43:56
3374	alert_queue (via created_time)	0	2026-02-10 15:43:56
3375	oshistory_detail (via dt)	0	2026-02-10 15:43:56
3376	monitor_data (via dt)	0	2026-02-10 15:43:56
3377	business_txn_avg (via dt)	0	2026-02-10 15:43:56
3378	int_profiling_hist (via from_time)	0	2026-02-10 15:43:56
3379	lama_application_metrics (via recorded)	0	2026-02-10 15:43:56
3380	lama_database_metrics (via recorded)	0	2026-02-10 15:43:56
3381	lama_db_bandwidth (via dt)	0	2026-02-10 15:43:56
3382	lama_db_latency (via dt)	0	2026-02-10 15:43:56
3383	lama_db_queue (via dt)	0	2026-02-10 15:43:56
3384	lama_db_status (via dt)	0	2026-02-10 15:43:56
3385	lama_disk_details (via dt)	0	2026-02-10 15:43:56
3386	lama_errors (via excep_at)	0	2026-02-10 15:43:56
3387	lama_hardware_metrics (via recorded)	0	2026-02-10 15:43:56
3388	lama_holidays (via dt)	0	2026-02-10 15:43:56
3389	lama_network_metrics (via recorded)	0	2026-02-10 15:43:56
3390	lama_networks_avg (via dt)	0	2026-02-10 15:43:56
3371	windisk_details (Verified: dt)	38763	2026-02-10 15:42:04
3372	processes_snaps (Verified: processinfo_time)	139	2026-02-10 15:42:04
3362	oshistory_detail (Verified: dt)	1440	2026-02-10 15:42:03
3363	monitor_data (Verified: dt)	1440	2026-02-10 15:42:03
3364	txn (Verified: started)	0	2026-02-10 15:42:03
3365	txn_slow (Verified: started)	0	2026-02-10 15:42:03
3366	int_profiling_hist (Verified: from_time)	0	2026-02-10 15:42:03
3367	alert_queue (Verified: created_time)	3	2026-02-10 15:42:03
3368	business_txn_avg (Verified: dt)	1440	2026-02-10 15:42:03
3369	intellitrace_errors (Verified: excep_at)	6	2026-02-10 15:42:03
3370	disk_io (Verified: dt)	0	2026-02-10 15:42:03
3193	mbean_multi_sensor_name (Skipped: Missing from_time &rl)	0	2026-02-10 15:40:14
3194	mbean_multi_sensor_prop (Skipped: Missing from_time &rl)	0	2026-02-10 15:40:14
3195	mbean_multi_sensor_value_temp (Skipped: Missing from_time &rl)	0	2026-02-10 15:40:14

Step 6: Use this query to list all active events within the **applicarearchive** schema.

```text
SHOW EVENTS FROM applicarearchive;
```



Db	Name	Definer	Time zone	Type	Execute at	Interval value	Interval field	Starts	Ends	Status	Originator	character_set_client	collation_connection	Database Collation
applicarearchive	daily_archive_at_1am	applicare@%	SYSTEM	RECURRING	NULL	1	DAY	2026-02-11 01:00:00	NULL	ENABLED	1	utf8mb4	utf8mb4_0900_ai_ci	utf8mb4_0900_ai_ci